

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 170 748 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
09.01.2002 Bulletin 2002/02

(51) Int Cl.7: G11B 33/04

(21) Application number: 01122491.2

(22) Date of filing: 11.04.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB IE IT LI NL PT SE

(30) Priority: 30.04.1996 GB 9608821
04.06.1996 GB 9611604

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
97916538.8 / 0 896 719

(71) Applicant: Dubois Ltd.
Corby, Northants. NN17 4AP (GB)

(72) Inventors:
• Pijanowski, Stefan Alexander
Oundle, Northants PE8 4EP (GB)

• Fraser, Anthony Henry Joseph
Corby, Northants NN17 3AB (GB)
• Farrar, Peter Antony
Ilkley, Leeds LS29 7LY (GB)

(74) Representative: Unwin, Stephen Geoffrey et al
Fry Heath & Spence, The Old College, 53 High
Street
Horley, Surrey RH6 7BN (GB)

Remarks:

This application was filed on 20 - 09 - 2001 as a
divisional application to the application mentioned
under INID code 62.

(54) Apparatus for holding a compact disk

(57) Apparatus for holding a compact disk having a
central hole, the apparatus comprising: a base portion;
a disk engaging and release mechanism extending from
the base portion for releasably engaging the central hole
of a disk comprising three equi-angularly spaced arms
each resiliently cantilevered from the base portion, the

inner ends of the arms together forming a button-like
member for releasably engaging the central hole of a
disk; and support means in the form of a raised surface
extending around the disk-engaging means and ar-
ranged to support the periphery of a disk mounted on
the apparatus during operation of the disk-engaging and
release mechanism.




Fig. 11

EP 1 170 748 A1

Description

TECHNICAL FIELD

[0001] This invention relates to apparatus for holding a compact disk. 5

[0002] By "compact disk", in the context of this specification, is meant not only the relatively common standard 120mm diameter laser-readable disk such as are currently sold carrying, for example, pre-recorded music, computer software and data, and similar recordable disks, but also similar disks of various sizes such as are known or proposed for recording video, films, interactive games and other information or data. 10

BACKGROUND ART

[0003] Conventionally, when not in use, such compact disks are stored in clear polystyrene boxes, known as "jewel cases", wherein the disk is held on a separate insert or tray fitted in the case and having seven or eight tines arranged to form a boss or "rosette" with which the aperture in the centre of a compact disk may be releasably engaged. 15

[0004] The legs or tines of the rosette are shaped such that they extend upwardly from the tray, curve outwardly, such that they can grip a compact disk, and then, towards their ends, curve inwardly to provide a boss over which the hole in the compact disk may be manually pushed. 20

[0005] It has long been recognised that such apparatus for holding a compact disk is not very satisfactory as it requires two hands to release a disk and lift it from the rosette: consequently many people do not attempt to push the centre of the rosette but instead use just one hand to grasp an outer edge of a compact disk and wrench it off the rosette thereby bending the disk, sometimes scoring the recorded surface of the disk on the tines, and eventually distorting or even breaking the tines. Such apparatus also does not retain the disk securely in that the disk can be released by lifting an edge thereof and may also be released due to shock loads, e.g. during transport, rough handling or if the apparatus is dropped or is subjected to an impact. 25

[0006] GB-A-2291640 and WO96/14636 disclose apparatus which overcomes many of the disadvantages of the prior art and the disclosure of both GB-A-2291640 and WO96/14636 is hereby incorporated in the present specification. 30

[0007] It has, however, been found that the apparatus disclosed in GB-A-2291640 and WO96/14636 can be further improved and that its construction can be further simplified. 35

[0008] One of the aims of the present invention is to reduce the risk of accidental release of a disk due to shock loads applied in the plane of the disk. 40

[0009] Another aim is to inhibit users from attempting to remove the disk by gripping the edge of the disk with-

out having depressed the release mechanism.

[0010] In conjunction with the above, another aim is to facilitate easy removal of a disk after the release mechanism has been depressed. 45

DISCLOSURE OF INVENTION

[0011] According to a first aspect of the invention, there is provided apparatus for holding a compact disk having a central hole, the apparatus comprising: a base portion and disk engaging means extending from the base portion for releasably engaging the central hole of a disk, the disk engaging means comprising at least two arms resiliently cantilevered from the base portion, the inner ends of the arms together forming a button-like member and each being provided with a projection arranged to securely retain a compact disk on the apparatus by engaging on an outwardly facing surface thereof, the arrangement being such that depression of the button-like member depresses the arms so as to move the projections towards each other until their 'engagement on the outwardly facing surface of the compact disk is released; an upstand being provided to surround or partially surround the peripheral edge of a disk whilst it is held by the disk engaging means and positioned sufficiently close to the periphery of the disk as to restrict the scope for movement of the disk within its own plane. 50

[0012] According to a second aspect of the invention, there is provided apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion and two arms resiliently cantilevered from the base portion extending radially inwards towards each other and away from the base portion, the inner end of each arm being provided with a projection and a contact portion, the projections being arranged to securely retain a compact disk on the apparatus by engaging on an outwardly facing surface thereof and the contact portions of the respective arms together forming a button-like member suitable for engagement by a finger tip, the arrangement being such that depression of the button-like member towards the base member causes the projections to move towards each other until their engagement with the outwardly facing surface of the compact disk is released, the contact portions being arranged such that should a force be applied to a disk held by the apparatus substantially in the plane of the disk and substantially perpendicular to the arms, at least the majority of said force is transmitted by the disk to only one of the contact portions so the possibility of such a force acting on the button-like member so as to release the disk is reduced. 55

[0013] According to another aspect of the invention, there is provided apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion provided with disk engaging means for releasably engaging the central hole of a disk and release means depression of which releases the disk from the disk engaging means whereupon the disk is moved to

a raised position further from the base portion, the base portion being provided with an upstand positioned so as to surround or partially surround the periphery of a disk held on the apparatus, recesses or cut-outs being provided in the upstand and being shaped so as to provide access to the edge of the disk when it has been released from the disk-engaging means but prevent or inhibit such access when the disk is held by the disk-engaging means.

[0014] According to a further aspect of the invention, there is provided apparatus for holding a compact disk having a central hole, the apparatus comprising: a base portion; a disk engaging and release mechanism extending from the base portion for releasably engaging the central hole of a disk comprising three equi-angularly spaced arms each resiliently cantilevered from the base portion, the inner ends of the arms together forming a button-like member for releasably engaging the central hole of a disk; and support means in the form of raised surface extending around the disk-engaging means and arranged to support the periphery of a disk mounted on the apparatus during operation of the disk-engaging and release mechanism.

[0015] Other features of the invention will be apparent from the following description and from the subsidiary claims of the specification.

BRIEF DESCRIPTION OF DRAWINGS

[0016] The invention will now be further described, merely by way of example, with reference to the accompanying figures, in which:

Figure 1 is a schematic plan view of a known release mechanism as described in GB-A-2291640;

Figure 2 is a plan view of a first embodiment of apparatus according to the present invention;

Figure 3 is a side cross-sectional view through the apparatus of Figure 2 with a disk shown held thereon;

Figures 4A - 4D are schematic plan views of alternative forms of release mechanism which may be used in place of that shown in Figure 2;

Figure 5 is a schematic plan view of part of apparatus such as that shown in Figure 2 showing a modification thereof;

Figures 6A and 6B are sectional views taken along line A-A of Figure 5;

Figure 7 is a plan view of apparatus similar to that shown in Figure 2 but with the modification illustrated in Figure 5;

Figure 8 is a plan view of another embodiment of apparatus according to the present invention;

Figure 9 is a perspective view of the apparatus shown in Figure 8;

Figure 10 is a plan view of a further embodiment of apparatus according to the present invention;

Figure 11 is a perspective view of the apparatus shown in Figure 10;

Figure 12 is a plan view of an alternative form of release mechanism which may be used in the apparatus shown in the preceding figures;

Figure 13A is a perspective view of the release mechanism of Figure 12; and

Figure 13B is a similar view but with some parts omitted so as to reveal other parts which are concealed in Figure 13A.

BEST MODE OF CARRYING OUT THE INVENTION

[0017] Figure 1 shows a plan view of two disk engaging arms 1 of prior art such as that disclosed in GB-A-2291640, cantilevered from a base portion 2 and connected thereto at hinge lines 3. The inner end of each arm is provided with a semi-circular contact portion 4 which together form a substantially circular button-like member over which the central aperture of a disk (not shown) is fitted. Each contact portion 4 carries a lip or projection 4A for securely retaining a disk by engaging on an outwardly facing surface thereof. The disk is released by depressing the button-like member towards the base portion which causes the contact portions 4 and hence the projections 4A to move towards each other until the engagement of the projections 4A on the disk is released.

[0018] Although this release mechanism functions satisfactorily, it can be improved in a number of ways, particularly to reduce the risk of accidental release of the disk therefrom.

[0019] One problem with the apparatus shown in Figure 1 is that if a force is applied in the plane of the disk in the direction A, i.e. perpendicular to the arms 1, this force causes the disk to engage both contact portions and apply forces to them as illustrated by the arrows B. Such forces tend to push both contact portions 4 inwardly, i.e. towards each other, and downwardly (towards the base portion 2) with the result that the disk can be released. In the example shown in Figure 1, the gap between the contact portions is relatively small but in real life the gap may be much wider so making this problem worse. This is a significant disadvantage as forces can be applied in the direction A due to mishandling of the disk or shock loads, e.g. if the apparatus is dropped or

receives a blow on the side.

[0020] It should be noted that references in this specification to forces applied to a disk include not only forces applied directly to the disk but also inertial forces which cause the disk to move in a similar way, e.g. when the apparatus is subjected to an impact.

[0021] It has been discovered that one way of reducing the possibility of the disk being released in this way is to arrange the contact portions 4 so that at least the majority of any force applied in the direction A is transmitted by the disk to only one of the contact portions 4.

[0022] This can be achieved by arranging the contact portions 4 so that the ends of the gap between them lie away from the perpendicular to the length of the arms 1. Figures 2 and 4 show various possible shapes of the contact portion 4 which achieve this.

[0023] There are a number of reasons why such an arrangement of the contact portions helps reduce the risk of the disk being released by forces applied within the plane of the disk and, in particular, in a direction perpendicular to the length of the arms 1. Firstly, as the force (or at least a majority of the force) A acts on only one of the contact portions, the tendency for the contact portions to be squeezed together is avoided or reduced. Also, as the gap between the contact portions 4 does not lie on this perpendicular, the contact portions can be formed to be a very close fit within the disk aperture in this direction so as to reduce the scope for lateral movement of the disk in this direction to a minimum.

[0024] Furthermore, if a force is applied in direction C shown in Figure 4A, i.e. at the end of the gap between the contact portions 4, the tendency for such a force to cause the disk to release compared with a force in direction A acting on the arrangement shown in Figure 1 is much reduced. Again, there are a number of reasons for this. As the gap between the contact portions is no longer perpendicular to the length of the arms 1, the width of the gap can be reduced as the inward movement of the contact portions 4 when the button-like member is depressed will be in a direction at an angle across the gap. The consequent reduction in the width of the end of the gap where the force C may be applied reduces the pinching effect of such a force as well as reducing the scope for movement of the disk perpendicular to the gap. Furthermore, a force in direction C will have a much reduced tendency to deflect the arm 1 as it is no longer perpendicular to the length of the arm 1. A force in direction C is resisted by the arm 1 as one component of the force is trying to stretch the arm. Furthermore, a force in direction C also acts to hold the disk more tightly under the projection 4A on that side of the button-like member and so the disk is retained more securely rather than having a tendency to be released.

[0025] It will be appreciated that the projections 4A are only provided on the side of the contact portion 4 in line with the arms 1 so they move inwardly when the button-like member is depressed to release the disk. For this reason, the prior art arrangement shown in Figure

1 is particularly vulnerable to a force applied in the direction A as such a force has no component which acts to hold the disk under either of the projections 4A.

[0026] As mentioned above, the contact portions 4A can have a variety of shapes to achieve the above advantages. The gap between the contact portions may be a simple straight line at, for example, approximately 45-70 degrees to the length of the arms 1 as shown in Figure 4A. Alternatively, the dividing line between the contact portions 4 may have a curved or sinusoidal shape. Figures 2 and 4B show examples of the latter where the contact portions 4 have a shape resembling the "yin-yang" symbol. The ends of these dividing lines still lie away from the perpendicular to the length of the arms 1 and are preferably positioned as close as possible to the arms 1.

[0027] Figure 4C shows a further arrangement in which the dividing line is substantially V or U-shaped and Figure 4D shows a further variant of this in which the dividing line follows a more curved form.

[0028] The width of the gap between the contact portions 4 is preferably 1.5mm or less and most preferably 1.0mm or less.

[0029] A further advantage of the arrangements described above is that the contact portions can be arranged to increase the likelihood that both portions are contacted when the button-like member is engaged by a finger tip (and so give more reliable operation of the disk release mechanism). If the diagonal dividing line shown in Figure 4A is arranged in the orientation shown so that it extends from the top left to the bottom right when a case incorporating the apparatus is open in the orientation shown in Figure 2, a right-handed person tends to extend their right index finger in a similar direction to this diagonal line so their finger tip will usually bridge the dividing line.

[0030] The other shape contact portions 4 shown in Figures 2 and 4B-4D are also designed so that, with a typical adult finger, it is difficult to press the button-like member without engaging both contact portions.

[0031] A yet further advantage of the arrangements described above, is that the dividing line between the contact portions, particularly in the central region of the button-like member, is no longer perpendicular to the length of the arms 1 so any tendency for a finger pressing the button-like member to be pinched by the gap as the contact portions 4 move towards each other is reduced. It will be appreciated that in the arrangements shown in Figures 4C and 4D, the dividing line does not pass across the central region of the button-like member so the possibility of the finger being pinched in this way is further reduced.

[0032] In addition to the above features, it is important to accurately form the button-like member so that it is a close fit within the central aperture of the disk (which, has a 15mm diameter in the conventional 120mm diameter disk) in order to minimise the scope for movement of the disk within the plane of the disk whilst it is held on

the apparatus. To this end, in the direction parallel to the length of the arms 1, the diameter of the button-like member immediately beneath the projection 4A when the disk is held thereon is preferably as close a match as possible to the diameter of the disk's aperture (which is typically 15mm) so as to avoid or minimise any play therebetween and avoid or minimise any stress applied to the aperture. Preferably the disk is free to rotate on the button-like member although lateral movement of the disk, i.e. within the plane of the disk, on the button is prevented or minimised.

[0033] In the direction perpendicular to the length of the arms 1, the contact portions 4 are again sized to be as close a fit as possible within the aperture of the disk so as to avoid or minimise the scope for movement of the disk in this direction and avoid or minimise any stress applied to the aperture.

[0034] The projections 4A preferably project from the sides of the contact portions and preferably project therefrom by between 0.5 and 1.0mm. Each projection also preferably extends around an arc on the edge of the respective contact portion so as to subtend an angle of between 30 and 90 degrees at the centre of apparatus.

[0035] The apparatus described herein has a number of other important differences over the apparatus described in GB-A-2291640.

[0036] GB-A-2291640 describes the use of resilient ejection means for urging the disk out of engagement with the disk engaging means when the rims or lips release their engagement on the disk, for example, further arms resiliently cantilevered from the base portion or one or more pieces of compressible material.

[0037] Such resilient ejection means may be used in the apparatus described herein. However, instead of or in addition to such resilient means, it has been discovered that the resilience of other parts of the apparatus, e.g. the arms 1 or the base portion 2, and, in particular, the resilience of the disk itself can be used to provide a similar ejection function. The apparatus is thus preferably arranged so that as the button-like member is depressed to release the disk, part of the apparatus and/or the disk is flexed so that elastic energy is stored therein and, when the engagement of the projections 4A is released, the said part and/or disk reverts to its unstressed state and causes at least the central portion of the disk to move so the projections 4A pass through the central aperture of the disk.

[0038] One simple way of achieving this is to provide supports 5 adjacent the periphery of the disk so that when the button-like member is depressed, the disk is moved towards the base portion 2 until its periphery engages the supports 5. Further depression of the button-like member to release the disk thus presses the centre of the disk towards the base portion 2 relative to the periphery of the disk whereby the disk undergoes elastic deformation. Once the projections 4A have moved inwardly sufficient to release their engagement on the out-

wardly facing surface of the disk, the disk is free to revert to its unstressed, flat shape whereupon the central portion of the disk moves, or "pops up", so it is not re-engaged by the projections 4A or button-like member when the user's finger is removed.

[0039] In the embodiment shown in Figure 2, support is provided at the periphery of the disk by raised surfaces 5 formed on the base portion 2.

[0040] The arrangement is preferably such that when a disk is held in the apparatus, the arms 2 support the disk clear of the support 5. The disk is thus held in an unstressed state and is free to rotate on the button-like member. Alternatively, the arrangement may be such that when a disk is held in the apparatus, the periphery of the disk is or is almost in contact with the support 5. It is also possible for the arrangement to be such that when a disk is installed on the apparatus it is held in a slightly flexed state and reverts to a flat shape when its engagement with the projections 4A is released.

[0041] Figure 3 shows a cross-sectional view of the apparatus shown in Figure 2 and shows a disk 10 held on the apparatus. This Figure shows the disk being held so that its periphery rests lightly on the supports 5 and the centre of the disk 10 is supported clear of the base portion 2 by the arms 1, preferably 2-3mm clear of the base portion 2.

[0042] The supports 5 also limit the extent by which the peripheral portion of the disk can be pressed towards the base portion. A further problem of the apparatus described in GB-A-2291640 is that by pressing the edge of the disk towards the base portion it is sometimes possible to prise the disk off the apparatus even though the button-like member has not been fully depressed. Accordingly, by limiting the scope for movement of the periphery of the disk towards the base portion, preferably in combination with an upstand (described further below) which limits the scope for lateral movement of the disk, this problem can be overcome or at least minimised.

[0043] The contact portions 4 may be mechanically interconnected, e.g. by a "living hinge" or a further button-like member. However, although this can be advantageous in some circumstances, it is not always possible or desirable. A living hinge can be formed between the contact portions if the apparatus is made of a resilient (typically crystalline) plastics material such as polypropylene and, indeed, this material is used to form apparatus as described herein when the apparatus is formed as an integral part of an enclosure for housing the disk. In some cases, such apparatus may, if desired, be provided with a mechanical interconnection between the contact portions, e.g. in the form of a living hinge, but in other cases no such interconnection is provided so the contact portions are separate from each other.

[0044] It is also desirable to form the apparatus described herein as an insert or "tray" for inserting within a separate casing. The conventional "jewel box" mentioned above comprises a clear plastics casing with the

disk-holding rosette formed on a tray inserted therein. The apparatus described herein may also be formed on a similar type of tray for inserting in a conventional clear plastics casing. Such inserts or trays are preferably made of an amorphous plastics material, such as styrene, as this has the required rigidity to hold its shape when formed into a relatively flat, tray-like article and is capable of being formed into more precise and intricate shapes. However, it is not always possible to form a living hinge that will survive repeated use in such a rigid material.

[0045] Accordingly, the apparatus described herein may also be provided in the form of an insert or tray formed from an amorphous plastics material with the respective contact portions 4 separate from each other but together forming a button-like member suitable for engagement by a finger tip. Nevertheless, in some circumstances, it is possible to form living hinges between the contact portions of apparatus formed of an amorphous plastics material.

[0046] An advantage of using contact portions 4 which are not interconnected, is that any tendency for one portion to pull the other one down if one portion is subjected to a lateral force such as A or C described above, is also avoided.

[0047] In such an arrangement, the contact portions 4 are also preferably shaped so as to increase the likelihood that both portions are contacted when the button-like member is depressed by a finger tip (as described above) to help ensure the release mechanism operates easily and reliably.

[0048] Another way of reducing the risk of accidental release of a disk due to forces applied in the plane of the disk, is to provide an upstand 6 surrounding or partially surrounding the disk when it is held in the apparatus so as to restrict access to the peripheral edge of the disk. The upstand 6 thus forms a "nest" in which the disk is held. The upstand 6 thus acts to obstruct access to much of the edge of the disk (except at finger cut-outs 6A which are provided to assist in lifting a disk out of the apparatus once it has been released) in order to further reduce the risk of forces being applied to the disk within the plane thereof. The upstand 6 is positioned close to the periphery of the disk (e.g. with a clearance of 0.5mm or less) so as to provide further restriction on the scope for movement of the disk within its own plane.

[0049] Such an upstand may be used in apparatus having any form of release mechanism, e.g. any of the forms illustrated in Figures 1 - 4 or described below with reference to Figures 8 - 13. The support 5 described above may be formed as a step in the side of the upstand 6.

[0050] In the arrangement shown in Figure 2, there is a gap in the upstand 6 at either side of the apparatus, each gap extending through about 40 degrees around the periphery of the disk. These gaps are provided to reduce the width of the apparatus. This is, for example, required so the apparatus made in the form of an insert

or tray can be fitted into an enclosure of conventional size. The disk is clearly more vulnerable to lateral forces in the area of these gaps. However, it will be appreciated that by shaping the contact portions 4 so that the ends of the gap between the contact portions fall on a line which does not coincide with the gaps in the upstand 6, this potential problem can be avoided. These gaps may also be closed by the sides of the container or its lid when this is closed. As the upstand 6 surrounds the majority of the disk and is positioned close thereto, it is still effective in reducing the scope for movement of the disk within its own plane despite the presence of these gaps.

[0051] The apparatus described herein thus enables a disk to be securely held by simply placing the disk on the apparatus so that its aperture lies over the button-like member. The disk is then pressed towards the base portion 2 whereupon the button-like member is depressed causing the contact portions 4 and the projections 4A to move towards each other until the button-like member is able to pass through the aperture. Once the projections 4A have passed through the aperture, the arms 1 revert to or towards their unstressed position so that the projections 4A engage upon the outwardly facing surface of the disk and thus securely retain the disk on the apparatus.

[0052] The apparatus is designed so that the disk can be easily released by depressing the button-like member but is otherwise very difficult to remove other than by forcing it to the extent that the apparatus and/or the disk is damaged.

[0053] Whilst held by the apparatus, the disk is supported away from the base portion 2 by the arms 1 and/or the button-like member. As the arms flex principally about the hinge lines 3 which are at a greater radius from the centre of the apparatus than the projections 4A, any attempt to prise or wrench the disk off the apparatus will cause the arms 1 to flex further from the base portion about the hinge lines 3 and thus tighten their engagement with the disk.

[0054] The arms 1 themselves are preferably relatively stiff so movement thereof occurs principally by means of flexing about the hinge lines 3 rather than flexing of the arm itself or of the contact portions 4 relative to the arm 1.

[0055] As indicated above, the disk is released by simply depressing the button-like member whereby the arms 1 flex towards the base portion 2. The disk itself must also be allowed to move towards the base portion 2 with the arms until the projections 4A have moved inwards sufficiently to release their engagement on the outwardly facing surface of the disk.

[0056] As described above, the shape of the contact portions 4 of the button-like member and/or the provision of an upstand immediately adjacent the edge of the disk help to reduce the risk of the disk being accidentally released by forces applied in the plane of the disk.

[0057] The apparatus shown in Figure 2 is preferably formed as an integral, one-shot plastics moulding.

[0058] Further improvements and features of the upstand 6 will now be described.

[0059] As indicated above, the apparatus is provided with an upstand 6 for surrounding or partially surrounding a disk held in the apparatus so as to restrict access to the peripheral edge of the disk. The upstand 6 thus acts to obstruct access to much of the edge of the disk, except at finger cut-outs 6A which are provided to assist in lifting a disk out of the apparatus when it has been released, to reduce the risk of forces being applied to the disk within the plane thereof. The upstand 6 is preferably positioned close to the periphery of the disk (eg with a clearance of 0.5mm or less) so as to restrict the scope for movement of the disk within its own plane.

[0060] A potential problem with apparatus such as that shown in Figure 2 is that users unfamiliar with the apparatus may be tempted to use the finger recesses 6A to try to grip the edge of the disk and attempt to wrench the disk off the button-like member without depressing the button-like member 4 and in doing so they are likely to damage the disk and/or the apparatus.

[0061] Figure 5 is a schematic plan view of a finger recess 6A similar to those shown in Figure 2 but which is formed such that when a disk 10 is held in the apparatus a part 6B of the upstand 6 extending across the finger recess 6A prevents or inhibits access to the edge of the disk 10 so that a user cannot use the finger recess to attempt to grip the disk by its edges.

[0062] Figure 6A is a cross-sectional view of the finger recess 6A shown in Figure 5 and shows the position of the disk when it is held by the disk-engaging means. As shown, the disk is preferably held just clear of the step or support 5 provided on the inner side of the upstand 6 but is at a position level with or beneath the top of the part 6B. The upstand 6, and the parts 6B thereof across the recesses 6A thus prevent access to the edge of the disk.

[0063] However, after the disk has been released from the disk-engaging means by depression of the button-like member 4, an ejection mechanism (as described above) causes the disk to be lifted so it is supported on or slightly above the button-like member 4 so that the periphery of the disk stands proud of the upstanding portion 6B as shown in Figure 6B. The user can then make use of the finger recesses 6A to grip the edge of the disk 10 in order to lift it from the apparatus.

[0064] It will be appreciated that, compared to the arrangement shown in Figure 2, the finger recesses shown in Figure 5 are modified so that they do not extend through to the inner side of the upstand 6 so the upstand 6 is not interrupted by the recesses. This is achieved by providing a relatively thin wall or upstand 6B across the inner end of each finger recess 6A as shown in Figure 5.

[0065] Figure 7 is a plan view of apparatus similar to that shown in Figure 2 but with the addition of walls 6B across the inner ends of the finger recesses 6A to prevent access to the periphery of the disk until the disk is

lifted clear of the walls 6B following release of the disk-engaging means.

[0066] As described above, to enable the disk 10 to be lifted from the apparatus it must be moved to a raised position following its release so that it stands proud of the part 6B of the upstand 6. It is found that access to the edge of the disk is sufficient to enable it to be lifted, it not being necessary for the user's fingers to engage the underside of the disk. Thus, to enable the disk to be lifted away from the apparatus it is merely necessary for the disk to be moved, following its release from the disk-engaging means, to a position where it stands just clear of the top of parts 6B of the upstand 6, preferably with the underside of the disk 10 just clear of the top of parts 6B.

[0067] The top of the parts 6B of the upstand may be at the same level as the top of the remainder of the upstand 6 or may be at a slightly lower position than the top of the remainder of the upstand 6.

[0068] When the disk 10 is held by the disk-engaging means, the upper surface of the disk 10 preferably lies at substantially the same level as the top of the parts 6B or may lie slightly below the level of the top of the remainder of the upstand 6 to prevent access to the edge of the disk 10. However, in other arrangements, when the disk 10 is held by the disk-engaging means, its upper surface may lie at a higher level than the top of the parts 6B as the form of the upstand 6 and/or recesses 6A may be such as to prevent a user's finger from being able to grip the edge of the disk as only the upper corner at the periphery of the disk can be touched. However, following release of the disk 10, it is lifted so the bottom surface of the disk 10 lies at a similar level to or above the level of the top of the parts 6B so the edge of the disk 10 can be gripped by a user's fingers.

[0069] Figures 8 and 9 show a further embodiment of apparatus for holding a compact disk. This embodiment is designed for holding a digital video disc (DVD) and the base portion 2 thus has a shape and size similar to that of a conventional video box.

[0070] The disk release mechanism illustrated in Figures 8 and 9 is similar to that described in GB-A-2291640 and WO96/14636. The two halves of the button-like member may be joined by a living hinge as shown or may be unconnected.

[0071] The upstand 6 shown in Figures 8 and 9 is similar to that of Figure 2 except that it is continuous, i.e. it extends the full 360 degrees around the periphery of the disk and, in the arrangement shown, no finger recesses are provided.

[0072] A support 5 is provided in the form of a step on the inner edge of the upstand 6 as in Figure 2 except this is also continuous, i.e. extends the full 360 degrees around the periphery of the disk.

[0073] The apparatus shown in Figures 8 and 9 functions in a manner similar to that shown in Figure 2. When a disk is held on the apparatus, the upstand, being positioned immediately adjacent the periphery of the disk,

obstructs access to the edge of the disk to prevent forces being applied to the disk in the plane thereof and to inhibit finger access to the edge of the disk and also serves to restrict scope for movement of the disk within the plane of the disk. It is therefore very difficult for the disk to be released from the mechanism either accidentally or intentionally other than by depressing the button-like member 4 at the centre of the disk.

[0074] When the button-like member 4 is depressed, the centre of the disk is flexed downwards by the action of the projections 4A of the button-like member 4 as the periphery of the disk is supported on the support 5 until the engagement of the projections 4A on the disk are released and the button-like member is able to pass through the central hole of the disk. The centre of the disk then "pops up" as the disk reverts to its flat, unflexed state whereby the centre of the disk is raised to prevent it being re-engaged by the button-like member when the user's finger is removed therefrom. The disk then rest lightly on the top of the button-like member 4 and its projections 4A and in this position its edges are held clear of the upstand 6 so a user's fingers can engage the edges of the disk to lift it away from the apparatus.

[0075] Figures 10 and 11 show another embodiment of apparatus for holding a compact disk similar to that shown in Figures 8 and 9 but with a 3-arm release mechanism instead of a 2-arm release mechanism, and mounted on a substantially square base portion 2 rather than a rectangular base portion. As shown, the three arms 1 are equi-angularly spaced from each other.

[0076] Each of the three arms 1 is cantilevered from the base portion 2 and connected thereto at a hinge line 3. The inner ends of the three arms 1 together form a button-like member comprising a triangular portion 20 each side of which is connected to a segment-shaped portion 21 by a living hinge 22. The three segment-shaped portions 21 together form a substantially complete circular shape over which the central hole of a disk 10 can be fitted. A lip or projection 21A for engaging on the outwardly facing surface of the disk 10 projects from the curved side of each segment-shaped portion 21. The lips 21A preferably project 0.5 - 1.0mm from the portions 21.

[0077] Depression of the triangular portion 20 towards the base portion 2 causes the three segment-shaped portions 21 to move towards each other, i.e. towards the centre of the triangular portion 20, until the projections 4A are moved out of engagement with the outwardly facing surface of the disk 10 so as to release their engagement with the disk. In all other respects, this apparatus functions in a similar manner to that shown in Figures 8 and 9.

[0078] The base portions 2 shown in Figures 8 - 11 may form part of a casing or may form a tray for insertion into a casing. In a further arrangement, the base portion 2 may be affixed, e.g. by adhesive to one half of a folded cover (not shown) e.g. formed of cardboard, the other half being arranged, when folded over, to cover a disk

held on the apparatus.

[0079] For the latter arrangement, the rear side of the base portion 2 is preferably substantially flat so as to facilitate its adhesion to the folded cover. The rear sides of the base portions shown in Figures 8 - 11 may be formed flat apart from a circular recess corresponding to the circular upstand 6 and a central cut-out where the release mechanism is formed.

[0080] A further upstand in the form of a wall 23 is provided around the periphery of the base portion 2. The wall 23 is preferably slightly higher than the upstand 6 so when the folded cover mentioned above is closed, the cover does not lie in contact with the disk. As shown in Figure 10, the wall 23 may form part of the upstand 6 where the upstand 6 meets the wall at the edge of the base portion.

[0081] Figure 12 is a plan view of another version of a 3-arm release mechanism which may be used in any of the other embodiments described above. In this case, the inner ends of the arms 1 are each provided with a sector-shaped portion 25 which together form a circular button-like member. The three sector-shaped portions 25 are separate from each other, i.e. they are not connected by living hinges. Each of the sector-shaped portions 25 has a projection 25A for engaging a disk.

[0082] Figure 13A is a perspective view of the 3-arm release mechanism shown in Figure 12. Figure 13B is a similar view but with the arms 1 and sector-shaped portions 25 omitted so as to more clearly show a three-armed re-inforcing portion 26 provided across the cut-out in the base portion 2 underneath the release mechanism.

[0083] The apparatus shown in Figures 10 and 11 is suitable for making in a resilient crystalline plastics material and the apparatus shown in Figures 12 and 13 is suitable for making in an amorphous plastics material.

[0084] In each of the embodiments described in relation to Figures 8 - 11, the upstand 6 is again preferably positioned so as to be immediately adjacent the edge of a disk held on the apparatus so as to prevent movement of the disk in its own plane and to provide the other functions described above.

[0085] Figures 8 - 11 show a continuous upstand 6 without finger recesses. However, in other arrangements (not shown) some areas of the upstand may be of slightly reduced height to facilitate finger access to the edge of the disk once it has been released so making it easier to grip the disk to lift it clear of the apparatus. Four localised areas of reduced height may, for instance, be provided in the upstand, each extending over a length of upstand subtending an angle of about 20 degrees at the centre of the apparatus. These areas are preferably equi-angularly spaced from each other and preferably located in areas of the upstand nearest the corners of the base portion 2.

[0086] In the apparatus described in relation to Figures 8 - 11, the support 5 preferably comprises a raised surface substantially parallel to the base portion (and to

the plane of a disk held thereon). The raised surface may, for instance, be at a level 2 - 3mm above the base portion 2 and have a width of about 2mm. The upstand 6 extends about 0.5 to 1.5mm, and preferably about 1mm, above the raised surface 5 (a compact disk typically has a thickness of about 1mm).

[0087] It should be noted that the degree of flexing of a disk required to cause the centre of the disk to rise or "pop up" sufficiently on release of the disk to prevent re-engagement thereof by the disk engaging mechanism may be relatively small. In some embodiments with a typical disk having a diameter of approximately 120mm the centre may be flexed approximately 0.5 - 1.0mm relative to the periphery thereof whereas in other embodiments the centre may flex 1.0 - 3.0mm. Similarly, the periphery of the disk need be raised by only a relatively small amount to lift it sufficiently relative to the upstand to enable the edges of the disk to be grasped. In some embodiments, this movement may be as small as 0.5 - 1.0mm whereas in other embodiments it may be 1 - 5mm.

STATEMENTS OF INVENTION

[0088]

1. Apparatus for holding a compact disk having a central hole, the apparatus comprising: a base portion and disk engaging means extending from the base portion for releasably engaging the central hole of a disk, the disk engaging means comprising at least two arms resiliently cantilevered from the base portion, the inner ends of the arms together forming a button-like member and each being provided with a projection arranged to securely retain a compact disk on the apparatus by engaging on an outwardly facing surface thereof, the arrangement being such that depression of the button-like member depresses the arms so as to move the projections towards each other until their engagement on the outwardly facing surface of the compact disk is released; an upstand being provided to surround or partially surround the peripheral edge of a disk whilst it is held by the disk engaging means and positioned sufficiently close to the periphery of the disk as to restrict the scope for movement of the disk within its own plane,

2. Apparatus as in 1 in which the upstand is positioned so as to leave a clearance between itself and the periphery of a disk held by the disk engaging means of 0.5 mm or less.

3. Apparatus as in 1 or 2 arranged such that, when a disk is held by the disk engaging means, at least the underside of the disk is held level with or beneath the top of the upstand and, when the engagement of the projections on the outwardly facing sur-

face of the disk is released, the disk is lifted so its periphery stands proud of the top of the upstand to allow a user's fingers to grip the edge of the disk.

4. Apparatus as in 3 in which resilient ejection means are provided to lift the disk once the engagement of the projections on the outwardly facing surface of the disk has been released.

5. Apparatus as in 3 provided with disk support means on the base portion for supporting the disk at positions away from the central hole, the arrangement being such that, when the disk is supported by the disk support means, the centre of the disk may be flexed towards the base portion such that upon release of the engagement of the projections on the outwardly facing surface of the disk, the disk is able to revert to an unstressed state so the centre of the disk moves out of engagement with the disk engaging means and the disk is lifted proud of the top of the upstand.

6. Apparatus as in 5 in which the disk support means comprises a step provided on the inner side of the upstand.

7. Apparatus as in any of 3 to 6 in which a plurality of recesses are provided in the upstand to facilitate finger access to the periphery of a disk once the engagement of the projections on the outwardly facing surface of the disk is released.

8. Apparatus as in 7 in which the recesses comprise localised reductions in the height of the upstand.

9. Apparatus as in 7 or 8 in which the recesses do not extend through to the inner side of the upstand.

10. Apparatus as in 9 in which a part of the upstand of reduced thickness relative to the remainder of the upstand extends across the inner side of each of the recesses.

11. Apparatus as in 10 in which the said part of the upstand of reduced thickness is of similar height or lower height than the remainder of the upstand.

12. Apparatus in which the disk engaging means comprises three arms resiliently cantilevered from the base portion.

13. Apparatus as in any of 1 to 11 in which the disk engaging means comprises two arms the inner end of each arm being provided with a contact portion, the contact portions together forming the button-like member, the contact portions being arranged such that should a force be applied to a disk held by the apparatus substantially in the plane of the disk and

substantially perpendicular to the length of the arms, at least the majority of said force is transmitted by the disk to only one of the contact portions so the possibility of such a force acting on the button-like member so as to release the disk is reduced.

14. Apparatus as in 13 in which the respective contact portions are separated by a gap, the ends of the gap lying away from a line which is perpendicular to the length of the arms.

15. Apparatus as in 14 in which a line joining the opposite ends of said gap lies at an angle of 45 to 70 degrees to the arms.

16. Apparatus as in 14 or 15 in which said gap forms a substantially straight dividing line between the contact portions.

17. Apparatus as in 14 or 15 in which said gap forms a curved dividing line between the contact portions.

18. Apparatus as in 17 in which said gap forms a substantially S-shaped dividing line between the contact portions.

19. Apparatus as in 14, 15 or 17 in which said gap forms a substantially V-shaped or U-shaped dividing line between the contact portions.

20. Apparatus as in any of 14, 15, 17 or 19 in which said gap does not pass through the central region of the button-like member.

21. Apparatus as in any of 14 to 18 in which a portion of said gap passing through the central region of the button-like member is not perpendicular to the arms.

22. Apparatus as in any of 14 to 19 in which the width of the gap is 1.5mm or less and preferably 1.0mm or less.

23. Apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion and two arms resiliently cantilevered from the base portion extending radially inwards towards each other and away from the base portion, the inner end of each arm being provided with a projection and a contact portion, the projections being arranged to securely retain a compact disk on the apparatus by engaging on the outwardly facing surface thereof and the contact portions of the respective arms together forming a button-like member, the arrangement being such that depression of the button-like member towards the base member causes the projections to move towards each other

until their engagement with the outwardly facing surface of the compact disk is released, the contact portions being arranged such that should a force be applied to a disk held by the apparatus substantially in the plane of the disk and substantially perpendicular to the arms, at least the majority of said force is transmitted by the disk to only one of the contact portions so the possibility of such a force acting on the button-like member so as to release the disk is reduced.

24. Apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion provided with disk engaging means for releasably engaging the central hole of a disk and release means depression of which releases the disk from the disk engaging means whereupon the disk is moved to a raised position relative to the base portion, the base portion being provided with an upstand positioned so as to surround or partially surround the periphery of a disk held on the apparatus, recesses or cut-outs being provided in the upstand and being shaped so as to provide access to the edge of the disk when it has been released from the disk-engaging means but prevent or inhibit such access when the disk is held by the disk-engaging means.

25. Apparatus for holding a compact disk having a central hole, the apparatus comprising: a base portion; a disk engaging and release mechanism extending from the base portion for releasably engaging the central hole of a disk comprising three equiangularly spaced arms each resiliently cantilevered from the base portion, the inner ends of the arms together forming a button-like member for releasably engaging the central hole of a disk; and support means in the form of raised surface extending around the disk-engaging means and arranged to support the periphery of a disk mounted on the apparatus during operation of the disk-engaging and release mechanism.

26. Apparatus as in 25 in which the base portion has a substantially flat rear face.

27. Apparatus as in 26 in which the rear face of the base portion is affixed to part of a folded cover.

28. Apparatus as in 25, 26 or 27 in which the button-like member comprises a triangular portion each side of which is connected to a segment-shaped portion provided at the inner end of each of the respective arms.

29. Apparatus as in 25, 26 or 27 in which the button-like member comprises three sector-shaped portions provided at the inner ends of the respective

arms.

30. Apparatus as in any of 25 to 29 in which the support means extends 360 degrees around the disk engaging means.

31. Apparatus in which the support means is at a level 2 to 3 mm above the base portion.

32. Apparatus as in any of 25 to 31 having an upstand extending around the outer edge of the support means so as to surround or partially surround the peripheral edge of a disk whilst it is held in the apparatus, the upstand being positioned sufficiently close to the periphery of the disk as to restrict the scope for movement of the disk within its own plane.

33. Apparatus as in 32 in which the support means comprises a step on the inner side of the upstand.

34. Apparatus as in any of 25 to 33 in which the base portion is square or rectangular and has an upstanding wall around the periphery thereof.

35. Apparatus in which the projections project from the respective contact portions.

36. Apparatus as in 35 in which the projections project from the respective contact portions by between 0.5 and 1.0mm.

37. Apparatus as in 35 or 36 in which the projections each extend around an arc which subtends an angle of between 30 and 90 degrees with the centre of the apparatus.

38. Apparatus as in 1 arranged such that when the button-like member is depressed and a disk is held on the apparatus, part of the apparatus and/or the disk is flexed so that elastic energy is stored therein such that when the engagement of the projections on the outer surface of the disk is released, said part and/or the disk reverts to its unstressed state so as to cause at least the central portion of the disk to move so the projections pass through the aperture of the disk.

39. Apparatus formed as a one-piece moulding.

40. Apparatus as in 39 moulded from a resilient plastics material.

41. Apparatus as in 40 in which the contact portions are mechanically interconnected.

42. Apparatus as in 39, 40 or 41 which is integrally moulded as part of an enclosure for a disk.

43. Apparatus as in 39 moulded from an amorphous plastics material.

44. Apparatus as in 39 in which the contact portions are separate from each other.

45. Apparatus as in 43 or 44 in which the apparatus is in the form of an insert or tray for inserting into an enclosure.

46. Apparatus for holding a compact disk substantially as hereinbefore described with reference to any one or more of Figures 2 to 13 of the accompanying drawings.

47. Apparatus having a compact disk held thereon.

Claims

1. Apparatus for holding a compact disk having a central hole, the apparatus comprising: a base portion; a disk engaging and release mechanism extending from the base portion for releasably engaging the central hole of a disk comprising three equi-angularly spaced arms each resiliently cantilevered from the base portion, the inner ends of the arms together forming a button-like member for releasably engaging the central hole of a disk; and support means in the form of a raised surface extending around the disk-engaging means and arranged to support the periphery of a disk mounted on the apparatus during operation of the disk-engaging and release mechanism.
2. Apparatus as claimed in Claim 1 in which the base portion has a substantially flat rear face.
3. Apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion and two arms resiliently cantilevered from the base portion extending radially inwards towards each other and away from the base portion, the inner end of each arm being provided with a projection and a contact portion, the projections being arranged to securely retain a compact disk on the apparatus by engaging on the outwardly facing surface thereof and the contact portions of the respective arms together forming a button-like member, the arrangement being such that depression of the button-like member towards the base member causes the projections to move towards each other until their engagement with the outwardly facing surface of the compact disk is released, the contact portions being arranged such that should a force be applied to a disk held by the apparatus substantially in the plane of the disk and substantially perpendicular to the arms at least the majority of the said force is trans-

mitted by the disk to only one of the contact portions so the possibility of such a force acting on the button-like member so as to release the disk is reduced.

4. Apparatus for holding a compact disk having a central hole, the apparatus comprising a base portion provided with disk engaging means for releasably engaging the central hole of a disk and release means depression of which releases the disk from the disk engaging means whereupon the disk is moved to a raised position relative to the base portion, the base portion being provided with an upstand positioned so as to surround or partially surround the periphery of a disk held on the apparatus, recesses or cut-outs being provided in the upstand and being shaped so as to provide access to the edge of the disk when it has been released from the disk-engaging means but prevent or inhibit such access when the disk is held by the disk-engaging means.

5

10

15

20

25

30

35

40

45

50

55




Fig. 1 (PRIOR ART)




Fig. 4A




Fig. 4B




Fig. 4C





Fig. 4D

Fig. 2






Fig. 3





Fig. 6A





Fig. 6B

Fig. 7






Fig. 8




Fig. 9




Fig.10




Fig. 11




Fig. 12




Fig. 13A




Fig. 13B

EP 1 170 748 A1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 2491

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	GB 2 291 640 A (DUBOIS PLC) 31 January 1996 (1996-01-31) * page 7, paragraph 3 - page 10, paragraph 2 *	3,4	G11B33/04
X	WO 92 06904 A (HANSEN DARRELL L) 30 April 1992 (1992-04-30) * page 6, line 3 - page 8, line 27 *	3,4	
A	---	2	
P,X	US 5 515 968 A (TANIYAMA YOSHIHIKO) 14 May 1996 (1996-05-14) * column 4, line 53 - column 5, line 13; figures 3-6 *	1-4	
A	EP 0 356 539 A (SHINETSU POLYMER CO) 7 March 1990 (1990-03-07) * column 3, line 17 - column 4, line 27 * * column 7, line 18 - line 50; figure 9 *	1,3,4	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G11B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 13 November 2001	Examiner Ressenaar, J-P
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : technological background O : non-written disclosure P : intermediate document & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 (2.9.97) (P4/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 2491

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-11-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2291640	A	31-01-1996	AT 170321 T	15-09-1998
			AU 715920 B2	10-02-2000
			AU 3811295 A	31-05-1996
			BR 9509593 A	30-09-1997
			CA 2204373 A1	17-05-1996
			CN 1171163 A	21-01-1998
			CZ 9701358 A3	16-12-1998
			CZ 20000222 A3	16-08-2000
			DE 69504364 D1	01-10-1998
			DE 69504364 T2	27-07-2000
			DK 789914 T3	25-05-1999
			EE 9700101 A	15-12-1997
			EP 0789914 A1	20-08-1997
			ES 2125054 T3	16-02-1999
			WO 9614636 A1	17-05-1996
			HK 186796 A	18-10-1996
			HU 77142 A2	02-03-1998
			JP 10502599 T	10-03-1998
			JP 11863317 A	03-03-1999
			NZ 294899 A	23-12-1998
			PL 319981 A1	01-09-1997
			SI 789914 T1	30-04-1999
			US 5788068 A	04-08-1998
			ZA 9509338 A	14-05-1996
WO 9206904	A	30-04-1992	WO 9206904 A1	30-04-1992
			EP 0554242 A1	11-08-1993
			JP 6501667 T	24-02-1994
US 5515968	A	14-05-1996	NONE	
EP 0356539	A	07-03-1990	EP 0356539 A1	07-03-1990
			US 4793479 A	27-12-1988

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

Online European Patent Register - Results

Status of the database as of 29-01-2002 (dd-mm-yyyy)

Choose your View: ☒ All data mentioned in Rule 92 and EPIDOS

[Return to Search Screen](#)

Publication numbers, publication type and publication dates

EP0896719 A2 06-11-1997 [1999/07]

WO9741563 06-11-1997 [1999/07]

Application numbers and filing date

Date of filing EP19970916538 (97916538.8)

11-04-1997 [1999/07]

WO1997GB01001

Date of publication of search report

Date of international search report

11-12-1997

International Searching Authority

EP

Priority number, priority date

GB19960008821 30-04-1996;

GB19960011604 04-06-1996 [1999/07]

Classification (IPC)

G11B33/04 [1999/07]

Designated states

AT , BE , CH , DE , DK , ES , FR , GB , IE , IT , LI , NL , PT , SE , FI [1999/07]

Extension of the patent

Country-code/date

payment/date withdrawal

LT/23-11-1998/00000000

Country-code/date

payment/date withdrawal

LV/23-11-1998/00000000

Country-code/date

payment/date withdrawal

SI/23-11-1998/00000000

English title

APPARATUS FOR HOLDING A COMPACT DISK [1999/07]

French title

DISPOSITIF POUR CONTENIR UN DISQUE COMPACT [1999/07]

German title

CD-HALTEVORRICHTUNG [1999/07]

Designated states, applicant name, address

FOR ALL DESIGNATED STATES

Dubois Ltd.

5 Princewood Road, Earlstrees Industrial Estate North

Corby, Northants. NN17 4AP/GB [1999/07]

Inventor name, address

01 / PIJANOWSKI, Stefan, Alexander / 24 Clifton Drive, Oundle / Northants PE8 4EP / GB

02 / FRASER, Anthony, Henry, Joseph / 4 Wilmington House, Highbury Crescent / London N5 1RU / GB

03 / FARRAR, Peter, Antony / Glenelg House, Gladstone Road / Rawdon, Leeds LS19 6HZ / GB [1999/07]

Representative name, address

Unwin, Stephen Geoffrey, et al

Fry Heath & Spence, The Old College, 53 High Street

Horley, Surrey RH6 7BN/GB [1999/07]

Filing language

EN

Procedure language

EN

Location of file and fax number for file inspection requests

Application is treated in (/fax-nr)

MUNICH/(+49-89) 23994465

PCT: Acts performed for entry into EPO regional phase

Acts performed for entry into the regional phase

23-11-1998

- National basic fee paid

23-11-1998

- Designation fee(s) paid

23-11-1998

- Examination fee paid

23-11-1998

Examination procedure

Date of request for preliminary

examination 26-11-1997
 request for examination 23-11-1998 [1999/07]
 Examination report(s) A.96(2), R.51(2)
 date dispatch/time-limit/reply 28-06-1999/M04/18-10-1999
 communication R.51(4)
 dispatched 01-12-2000
 - approval (yes or no) no
 - later approval 20-09-2001
 communication R.51(6)
 dispatched 09-10-2001
 Refusal of application
 decision (refusal) A.97(1)
 date dispatch/legal effect date 20-07-2001/00000000
Application withdrawn or deemed to be withdrawn
 Request for further processing A.121
 - date of filing / fee payment 20-09-2001 / 20-09-2001
 - decision / date request accepted / 09-10-2001
Divisional Application(s)
 Divisional
 application/publication number
 (s) EP20010122491/EP1170748
Renewal fees
 Renewal fee A.86 (patent
 year / paid) 03/06-04-1999
 04/05-04-2000
 05/03-04-2001
Documents cited in the European Search
 [] See references of WO 9741563A1
Documents cited in the International Search
 WO9614636 A [XP];
 US5515968 A [XP];
 GB2291640 A [Y];
 WO9206904 A [Y];
 EP0356539 A [A];
 US5558220 A [AP];
 DE3425579 A [A]
 [End of Data]

Return to Search Screen
 30-01-2002 14:18:03